

CORRUGATED METAL HOSE WITH SS BRAIDING

APPLICATION:

Suitable for high pressure hot water, steam, hot oils, oxygen etc.
Loading and unloading of tankers with gas, chemicals and other system on diesel and petrol motors.

CONSTRUCTION:

Stainless steel corrugated metal hose with braiding offered in austenitic steel.

TEMPERATURE RANGE:

-269°C - +600°C.



Code	Nominal Bore	Minimum Bend Radius		Single Braid		Double Braid	
		N.B. MM	Static MM	Flexing MM	Max. Pressure Kg/cm ²	Test Pressure Kg/cm ²	Max. Pressure Kg/cm ²
SM006	6	25	100	100	150	160	240
SM010	10	40	150	90	135	144	216
SM012	12	50	200	80	120	128	192
SM020	20	70	200	64	96	102	153
SM025	25	90	200	50	75	80	120
SM032	32	110	250	40	60	64	96
SM038	40	130	250	30	45	48	92
SM050	50	175	350	28	42	44	66
SM063	63	200	410	24	36	38	57
SM076	76	205	450	18	27	28	42
SM100	100	230	560	16	24	26	39
SM150	150	320	816	10	15	16	24

AVAILABLE IN:

- FOOD GRADE
- DOUBLE BRAID
- VACCUM